

Roger 17

(02)

Technical Data

roger



Roger 17 is a design-integrated Roger receiver that is designed for use with the Advanced Bionics Naída CI Q70 sound processor.

Simply attach the Roger 17 receiver to the Naída CI sound processor. When the speaker uses a Roger wireless microphone, Naída CI recipients have the opportunity to benefit from industry-leading speech-in-noise performance.

Roger 17 features

- Adaptive gain
- Effective stand-by mode
- EasyGain adjustment
- Check to read / manage device data via Roger inspiro
- Link quality measurement

What is Roger

Roger is the new digital standard that bridges the understanding gap, in noise and over distance, by wirelessly transmitting the speaker's voice directly to the listener.

General data

Type:	Design-integrated Roger CI receiver Operates with all Roger microphones
Length:	18.7 mm / 0.736 inch
Width:	9 mm / 0.354 inch
Height:	10.6 mm / 0.417 inch
Weight:	0.94 g / 0.032 oz
Operating conditions:	The product has been designed for trouble-free operation without restrictions when used as intended, unless otherwise stated in the user guide. 0° to +60° Celsius / +32° to +140° Fahrenheit and relative humidity < 95% (non condensing)
Transport and storage conditions:	-20° to +60° Celsius / -4° to +140° Fahrenheit and relative humidity of 90% for a long period of time



Roger characteristics

Frequency:	2.4 GHz including adaptive automatic frequency hopping
Transmission delay:	< 20 ms
Antenna:	Built-in antenna
Backlink RF power:	< 10 mW / MHz

Audio characteristics

Audio bandwidth:	100 Hz – 7.2 kHz
Distortion:	< 2% for $f_{mod} = 1$ kHz
Audio signal output:	-54 dBV (transmitter in compression, $f_{mod} = 1$ kHz, surrounding noise level < 58 dB SPL)
Adaptive audio gain:	Up to 20 dB
EasyGain range:	-8 dB to +8 dB

Power management

Power supply:	Supplied by the CI sound processor battery
Voltage range:	1.0 to 1.5 V
Current drain:	Active mode < 3.4 mA for $V_{BAT} = 1.2$ V Sleep mode < 700 μ A for $V_{BAT} = 1.2$ V

Standards

Radiocom:	EN 300 440 FCC part 15.249
EMC:	EN 60601-1-2, EN 301 489 FCC part 15b
Water Resistant:	IP54 ¹

Housing colors



Sand Beige (P1)



Chestnut (P4)



Silver Gray (P6)



Velvet Black (P8)



Ruby (P9)



Petrol (Q1)



Alpine White (XN)



Princess Pink (XP)



Electric Green (Q2)



Caribbean Pirate (Q3)



Dragon Orange (Q4)



Vanity Pink (Q5)

¹ IP54 indicates that splashing water from any direction for 5 min had no harmful effect on the CI sound processor and attached Roger receiver.